



**R-410a STANDARD
EFFICIENCY CONDENSER**



R-410a STANDARD EFFICIENCY CONDENSER

PERFORMANCE YOU CAN RELY ON

FEATURES

- Painted Galvanized steel cabinet
- Coil with Aluminum enhanced fins & copper tubing
- Inner groove tubes for better heat transfer and higher efficiency
- Scroll compressor
- For use in R-410a



Model		LAC024-100P431	LAC036-100P431	LAC048-100P431	LAC060-100P431
OUTDOOR MODEL	COOLING DATA 208-230 / 1/60				
	VOLTAGE	220-230V,1Ph,60Hz	220-230V,1Ph,60Hz	220-230V,1Ph,60Hz	220-230V,1Ph,60Hz
	NOMINAL COOLING CAP. (BTUH)	24000	36000	48000	60000
	SEER	10	10	10	10
	CONNECTION LIQUID (INCHES)	3/8	3/8	3/8	3/8
	CONNECTION GAS (INCHES)	5/8	3/4	3/4	3/4
	MAX CURRENT (A)	17.5	25.5	30.7	34.6
SOUND LEVEL	65	65.5	64.7	64.4	
PHYSICAL DATA	UNIT DIMENSION S HXWXL (MM)	600x600x633	600x600x759	710x710x759	710x710x843
	BOXED UNIT DIMMENSIONS HXWXL (MM)	628x628x667	628x628x794	738x738x794	738x738x872
	GROSS WEIGHT (KG)	50.8	61.4	76.1	85

Model		LAC036-100Y431	LAC048-100Y431	LAC060-100Y431
OUTDOOR MODEL	COOLING DATA 208-230 / 1/60			
	VOLTAGE	220-230V,3Ph,60Hz	220-230V,3Ph,60Hz	220-230V,3Ph,60Hz
	NOMINAL COOLING CAP. (BTUH)	36000	48000	60000
	SEER	10	10	10
	CONNECTION LIQUID (INCHES)	3/8	3/8	3/8
	CONNECTION GAS (INCHES)	3/4	3/4	3/4
	MAX CURRENT (A)	15.0	18.1	23.4
SOUND LEVEL	65.5	64.7	64.4	
PHYSICAL DATA	UNIT DIMENSION S HXWXL (MM)	600x600x759	710x710x759	710x710x843
	BOXED UNIT DIMMENSIONS HXWXL (MM)	628x628x794	738x738x794	738x738x872
	GROSS WEIGHT (KG)	60.6	74	85



LENNOX

Visit us at www.lennoxglobal.com or call +1-305-718-2901
 © 2018 Lennox Industries Inc.
 For a complete list of the registered and common law trademarks
 owned by Lennox Industries Inc., please visit www.lennox.com
 ECPI-R-22-10SEER01EN-011018

Distribuido por: