



SUBMITTAL DATA - OUTDOOR UNIT

VER096C432Y

VRF HEAT RECOVERY

208-230/3/60

Job Name: _____
 Location: _____
 Schedule No.: _____
 System Designation: _____

Engineer: _____
 Architect: _____
 Date: _____
 For: ___ Reference ___ Approval ___ Review ___ Construction

FEATURES

- Three-pipe heat recovery
- Accelerated complete coil defrost
- Hermetically sealed compressor with crankcase heater
- Thermal and Current protection in Compressor
- Steel casing with baked enameled finish Compressor
- Access to electrical box for ease of maintenance
- High efficiency DC Inverter Scroll compressor
- Compressor mounted on vibration isolation pads
- Plastic Fan Blade
- Intelligent duty cycle operation
- Hydrophilic Aluminum Gold Fin
- Subcooling Control Technology

PRODUCT WARRANTY

Compressor - Seven year limited warranty
 All other components - Five year limited warranty

SPECIFICATIONS

PERFORMANCE

Cooling Capacity (95°F)* (Btu/h)		92,000	
EER (95°F)	(W/W)	Ducted	3.22
		Non Ducted	3.28
		Mixed	3.25
	(Btu/h)/W	Ducted	11.00
		Non Ducted	11.20
		Mixed	11.10
IEER	(Btu/h)/W	Ducted	20.50
		Non Ducted	23.50
		Mixed	22.00
Cooling Power Input (W)		7,300	
Heating Capacity (47°F)* (Btu/h)		100,000	
COP (47°F)	(W/W)	Ducted	3.30
		Non Ducted	3.50
		Mixed	3.40
Heating Capacity (17°F)* (Btu/h)		67,000	
COP (17°F)	(W/W)	Ducted	2.25
		Non Ducted	2.40
		Mixed	2.33
Heating Power Input (W)		7,850	

ELECTRICAL DATA

Power Supply	208-230/3/60
MOCP (A)	45
MCA (A)	37
No. of Compressors	1
No. of Fans	2

GENERAL DATA

Combination Ratio Indoor / Outdoor	50% to 135%
Max. # of Indoor Units	16
Sound Pressure Level (dBA)/Sound Power Level	62/72
Refrigerant Type	R410a
Factory Refrigerant Charge (oz)	395.1

DIMENSIONS

Unit Dimensions (in)	Height	63 1/4
	Width	52 3/4
	Depth	30 1/8
Liquid Pipe Connection (in)	3/8	
Low Pressure Gas Pipe Connection (in)	7/8	
High Pressure Gas Pipe Connection (in)	3/4	
Shipping Weight (lb)	716	
Net Weight (lb)	683	



NOTES:

*Cooling and Heating Capacity data AHRI-1230-2010 conditions




NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency. ©2019 Lennox Industries Inc.







SUBMITTAL DATA - OUTDOOR UNIT
VER096C432Y
VRF HEAT RECOVERY
208-230/3/60

DIMENSIONAL DRAWINGS



② Installation hole



NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency. ©2019 Lennox Industries Inc.