

			Standard indoor floor ceiling		
Indoor Model			LXGUCMD036100P20-3	LXGUCMD048100P20	LXGUCMD060100P20-3
Indoor code			Y5796	Y5797	Y5798
Outdoor Model					
Outdoor code					
Power supply		V-ph-Hz	220~230-1-60	220~230-1-60	220~230-1-60
Cooling	Capacity	Btu/h	36000	46000	54000
	Input	W	4040	4970	6130
	EER	W/W	2.61	2.71	2.58
Heating	Capacity	Btu/h	/	/	/
	Input	W	/	/	/
	COP	W/W	/	/	/
Indoor fan motor	Model		YSK115-4B	YSK115-4B	YSK85-4B
	Qty		1	1	2
	Input	W	235/200/172	235/200/172	174/157/144
	Capacitor	uF	5UF/450V	5UF/450V	2.5UF/450V
	Speed(Hi/Med/Lo)	r/min	1320/1175/1050	1320/1175/1050	1400/1220/1090
Indoor air flow(Hi/Med/Lo)		m ³ /h	1900/1700/1500	2000/1700/1500	2400/2100/1800
Indoor noise level (sound pressure)(Hi/Med/Lo)		dB(A)	53/50/46	52/48/45	57/53/50
Throttle type			Throttle valve	Throttle valve	Throttle valve
Indoor unit	Dimension (WxDxH)	mm	1285x675x235	1285x675x235	1650x675x235
	Packing (WxDxH)	mm	1360x755x313	1360x755x313	1725x755x313
	Net/Gross weight	kg	32/37.5	33/39	39/45
Design pressure		MPa	2.6/1.0	2.6/1.0	2.6/1.0
Drainage water pipe diameter		mm	ODΦ25	ODΦ25	ODΦ25
Refrigerant piping	Liquid side/Gas side	mm(inch)	Φ9.52/Φ19(3/8"/3/4")	Φ9.52/Φ19(3/8"/3/4")	Φ9.52/Φ19(3/8"/3/4")
Controller			Remote-RG51Q1/BGE	Remote-RG51Q1/BGE	Remote-RG51Q1/BGE
Operation temperature		°C	17~30	17~30	17~30
Room temperature	Cooling	°C	17~32	17~32	17~32
	Heating	°C	/	/	/
Qty' per 20' /40' /40'HQ (indoor unit)			92/188/213	92/188/213	72/147/167