

CASED FAN COIL

Convenient, localized
heating and cooling

R-410A OR
R22 REFRIGERANTS



LENNOX

America's Premier Climate Comfort Brand since 1895

Rugged, reliable comfort anywhere

Lennox® cased fan coils make it simple to bring powerful heating and cooling to areas that would be otherwise difficult to keep comfortable. Designed with durability in mind, they include smart touches like galvanized steel for corrosion resistance.

Features for your convenience and comfort

Auto restart automatically restores previous settings if power is turned off and then on again.

Sleep mode avoids overheating or overcooling during the night.

24-hour on/off timer for added convenience.

Easy installation makes Lennox® cased fan coils a smart solution anywhere.

Anti cold air preheats copper piping to prevent a rush of cold air during heating operation.

Comfort controls for adjustment of cooling and heating output. Coil is available with wall-mounted control and remote control for added convenience.

Internal self-monitoring system detects errors and displays operational status via LED.

Fixed-speed operation provides consistent heating and cooling output.



Models and performance specifications

	MODEL #	Voltage	Nominal Cooling [Btu/H]	Nominal Heating [Btu/H]	Refrigerant Type	Packing Dimensions W x D x H [mm]	Indoor Unit Weight [kg]	Air Flow (H/M/L) [M ³ /H]	Noise Rating [dB]
COOLING ONLY	LXG FCCMD018100P6	230/1/60	18,000	—	R22 or R-410A	1,135 x 655 x 290	30	1,170/770/650	44/31/26
	LXG FCCMD024100P6	230/1/60	24,000	—	R22 or R-410A	1,135 x 655 x 350	33.5	1,400/1,100/1,000	44/35/32
	LXG FCCMD030100P6	230/1/60	30,000	—	R22 or R-410A	1,135 x 655 x 350	33.5	1,800/1,600/1,400	45/43/40
	LXG FCCMD036100P6	230/1/60	36,000	—	R22 or R-410A	1,355 x 795 x 350	47	2,270/1,890/1,650	46/44/42
	LXG FCCMD048100P6	230/1/60	48,000	—	R22 or R-410A	1,385 x 920 x 373	55	3,010/2,410/1,940	46/43/41
	LXG FCCMD060100P6	230/1/60	60,000	—	R22 or R-410A	1,385 x 920 x 373	55	3,150/2,510/1,990	46/42/40
HEAT PUMP	LXG FHCMD018100P6	230/1/60	18,000	20,000	R22 or R-410A	1,135 x 655 x 290	30	1,170/770/650	44/31/26
	LXG FHCMD024100P6	230/1/60	24,000	26,000	R22 or R-410A	1,135 x 655 x 350	33.5	1,400/1,100/1,000	44/35/32
	LXG FHCMD036100P6	230/1/60	36,000	40,000	R22 or R-410A	1,355 x 795 x 350	47	2,270/1,890/1,650	45/42/40
	LXG FHCMD048100P6	230/1/60	48,000	52,000	R22 or R-410A	1,385 x 920 x 373	55	3,010/2,410/1,940	46/43/41
	LXG FHCMD060100P6	230/1/60	60,000	65,000	R22 or R-410A	1,385 x 920 x 373	55	3,150/2,510/1,990	46/43/41

Note: Due to Lennox' ongoing commitment to quality, all specifications, ratings and dimensions are subject to change without notice.



America's Premier Climate Comfort Brand since 1895

Visit us at www.lennox.com, or contact us at 1-877-726-0024.

© 2013 Lennox Industries Inc.
For a complete list of the registered and common law trademarks owned by Lennox Industries Inc., please visit www.lennox.com.

(10T04) 06/13 PC74985