



SUBMITTAL DATA - OUTDOOR UNIT
VEP036C432P
MINI VRF HEAT PUMP
208-230/1/60

Job Name: _____
 Location: _____
 Schedule No.: _____
 System Designation: _____

Engineer: _____
 Architect: _____
 Date: _____
 For: ___ Reference ___ Approval ___ Review ___ Construction

FEATURES

- Two-pipe heat pump
- Automatic Defrost
- DC Motor
- Gold Fin
- Direct Driven Fan Motor
- Drive Board Overload Protection
- Electronic Expansion Valve
- Flared Connections
- Copper Tube - Aluminum Fin

PRODUCT WARRANTY

Compressor - Seven year limited warranty
 All other components - Five year limited warranty

SPECIFICATIONS

PERFORMANCE

Cooling Capacity* (Btu/h)		37,800
EER (W/W)		3.73
EER (Btu/h)/W (95F)		10.00
Cooling Power Input (W)	Ducted	3,250
	Non Ducted	2,700
Heating Capacity* (Btu/h)		42,000
COP (W/W)		3.95
COP (KBtu/h)/W		10.59
Heating Power Input (W)	Ducted	3,720
	Non Ducted	2,820
SEER		16

ELECTRICAL DATA

Power Supply (V / Ph / Hz)	208-230/1/60
MOCB (A)	35
MCA (A)	31
Circuit Breaker Capacity (A)	50

GENERAL DATA

Combination Ratio Indoor / Outdoor	50% to 125%
Max. # of Indoor Units	7
Sound Pressure Level (dBA)	55
Refrigerant Type	R410a
Factory Refrigerant Charge (oz)	176.4
Compressor Type/Qty	Inverter Rotary / 1
Fan Type/Qty	Axial / 2

DIMENSIONS

Unit Dimensions (in)	Height	53
	Width	35 1/2
	Depth	13 3/8
Liquid Pipe Connection (in)		3/8
Gas Pipe Connection (in)		5/8
Drain Pipe Connection (in)		0.33
Shipping Weight (lb)		264.6
Net Weight (lb)		242.6



NOTES:

*Cooling and Heating Capacity data AHRI-1230-2010 conditions




NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency. ©2019 Lennox Industries Inc.



SUBMITTAL DATA - OUTDOOR UNIT
VEP036C432P
MINI VRF HEAT PUMP
208-230/1/60

DIMENSIONAL DRAWINGS



	mm	in
Height	1345	53
Width	900	35 1/2
Depth	340	13 2/5
A	378	14 8/9
B	572	22 1/2

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency. ©2019 Lennox Industries Inc.